

1 CHIP HD CAMERA WITH USB



TEKNO CAM 1000 HD USB

tk 754-2000 USBHD

without objective



Technical data

- Sensor: 1 x 1/3" MOS Sensor
- Pixel: 1920 x 1080p Pixel (FULL HD)
- Resolution: > 1000 lines
- Sensitivity: < 3 Lux
- Signal noise ratio: 54 dB
- Shutter: 1/50 to 1/10.000 sec.
- Video outputs
 - Analogue: 1 x RGB / YPbPr, 1 x S-Video (Y/C), 1 x BNC
 - Digital: 1x HDMI / DVI, 2 x HD-SDI (optional)
 - Archiving: 1 x USB - Front
 - Others: 1x Remote IN / 1x Remote OUT / 1x PS/2
- Picture format: 16:9, JPG (1920 x 1080)
- Video format: Full HD 1920 x 1080p, Mpeg4 (H.264 Codec)
- Easy storage with USB drive
- 3 Preselectable remote buttons on camera head (6 functions)
- 3 Memories for user profiles
- Automatic storage of last configuration
- Automatic white-balance
- C-Mount camera head soakable
- Digital Zoom (2.5 x)
- Patient data import by text generator
- Freeze
- In combination with our FLOW-S insufflators, the actual gas flow may be displayed on the monitor
- Line voltage: 100 - 240 VAC; 50 - 60 Hz
- Power consumption (max.): 22W
- Dimensions (W x H x D): 353 x 103 x 253 mm
- Dimensions camera head (Ø; Length): Ø 34 mm; 73 mm
- Weight camera: approx. 4.7 kg
- Weight camera head: approx. 97g
- Produced and tested acc. to IEC 601-1; EN 60601-1
- CE marking acc. to RL 93/42/EWG